



OVER 1 MILLION SOLD!



CNC PIPE THREADING LATHE



HIGH PRECISION | RELIABLE | EFFICIENT

Represented by Shanghai Jingoo Petroleum Apparatus Co., Ltd.

SPECIFICATIONS

Item	Unit	STC18 Series	STC22 Series	STC34 Series
Capacities				
Max Swing Dia. Over Bed	mm	630	800	900
Max Cutting Length	mm	350 (400 is Opt.)	1000/3000	1000/1500/3000
Max Cutting Dia.	mm	180	219 (Electric Chuck)	340
Petroleum Application	Inch	2 3/8 " - 7 "	4 1/2 " - 8 5/8 "	4 1/2 " - 13 3/8 " (Electric chuck) 5 " - 13 3/8 " (Hydraulic chuck)
Spindle				
Spindle Speed Range	r/min	90-610 (Servo motor)	90-450 (Servo motor)	90-350 (Servo motor)
Main Motor Power	kW	22 (Servo motor)	22 (Servo motor)	22(Servomotor)/ 30(Servomotor)
Spindle Bore Dia.	mm	205	240 (Electric chuck)	355
Feed System				
X/Z axis Rapid Traverse	m/min	4/8	4/8	4/8
X-axis Travel	mm	300	300	300
Z-axis Travel	mm	350 (400 is Opt.)	1000/3000	1000/1500/3000
General				
Std. Turret	-	Vertical 4-station turret 32×32	Vertical 4-station turret 40×40	Vertical 4-station turret 40×40

Shanghai Jingoo Petroleum Apparatus Co., Ltd.

Office: Room 103, Meilin Creative Park A3,
#228 Banting Road, Songjiang District,
Shanghai, China

Postcode: 201615

Phone: +86-21-51098802

Email: sales@jingooapigage.com

Website: www.jingooapigage.com

Note : - Specifications are subject to change without further notice.

- Image is the representation of the machine, not necessarily a photograph.